



(12) **EUROPEAN PATENT SPECIFICATION**

(45) Date of publication and mention  
of the grant of the patent:  
**09.10.2002 Bulletin 2002/41**

(51) Int Cl.7: **B60T 17/00, B01D 53/26**

(86) International application number:  
**PCT/US96/12163**

(21) Application number: **96925452.3**

(87) International publication number:  
**WO 97/003872 (06.02.1997 Gazette 1997/07)**

(22) Date of filing: **24.07.1996**

(54) **AIR DRYER CARTRIDGE MOUNTING SYSTEM**

**BEFESTIGUNGSSYSTEM EINER LUFTTROCKNUNGSPATRONE**

**SYSTEME DE MONTAGE D'UNE CARTOUCHE DE DESSICATEUR D'AIR**

(84) Designated Contracting States:  
**DE FR GB IT**

(72) Inventor: **BLEVINS, Jerry, Richard**  
**Bloomfield Hills, MI 48301 (US)**

(30) Priority: **24.07.1995 US 506313**

(74) Representative: **Weber, Dieter, Dr.**  
**Weber, Seiffert, Lieke**  
**Postfach 61 45**  
**65051 Wiesbaden (DE)**

(43) Date of publication of application:  
**13.05.1998 Bulletin 1998/20**

(73) Proprietor: **Bendix Commercial Vehicles**  
**Systems, LLC**  
**Elyria, Ohio 44035 (US)**

(56) References cited:  
**EP-A- 0 234 229 DE-A- 4 339 758**  
**US-A- 4 487 617**

**EP 0 840 686 B1**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

## Description

### BACKGROUND OF THE INVENTION

[0001] This invention relates to a component for a motor vehicle air brake system, and particularly, to an air dryer assembly.

[0002] Many motor vehicles, and in particular, heavy duty trucks incorporate air brake systems which use air pressure to control application of the vehicle service brakes. These systems have an air compressor driven by the vehicle engine which charges a brake system reservoir with high pressure air. The air compressor is controlled to supply air intermittently as needed to replenish the reservoir and maintain reservoir pressure within a predetermined range.

[0003] The process of compression of air results in the precipitation of water. Water and particulates in the air brake system can lead to component deterioration and interfere with optimal operation of the brake system. Accordingly, there are various devices used for removing water from the compressed air in air brake systems, known as air dryers. The function of an air dryer is to collect and remove air system contaminants in solid, liquid and vapor form before they enter the brake system. The air dryer provides clean, dry air for the components of the brake system which increases the life of the system and reduces maintenance costs. One type of air dryer incorporates a desiccant material which eliminates daily manual draining of water collection reservoirs as is required in other types of air dryers.

[0004] Desiccant type air dryers employ a volume of desiccant material which is hydrophilic and thus absorbs water which passes through an air line from the air compressor. High pressure air enters the desiccant air dryer and the water is stripped by the desiccant material. The air dryer also includes a particulate filter for trapping particulates and oil. Eventually, the desiccant material absorbs water to its maximum capacity. As a means of expelling this trapped water, modern desiccant type air dryers incorporate a backflow or purge air flow as a means of stripping the desiccant of absorbed water. A reservoir referred to as a purge volume is provided with is charged with the high pressure air supplied by the compressor. When the compressor cycles from a loaded mode producing compressed air to the unloaded mode, the purge volume air is allowed to leak to atmosphere through the desiccant bed in a reverse flow direction, stripping it of moisture and expelling it into the air. External purge volume air dryer types use a purge volume reservoir separate from the air dryer and connected to it by an air line. Another type is a so-called integral purge volume type in which the housing which contains a desiccant material also defines the purge volume. These types are in widespread use today and provide excellent performance.

[0005] In modern desiccant type air dryers some means of removing the desiccant material is provided

since it requires rejuvenation after a service life period. In use, the desiccant material absorbs contaminants such as oil which ultimately reduces its water retention characteristics. Since other components of air dryers have a long service life, a convenient system for removing the desiccant material is desired. In one type of air dryer, spin-on type desiccant cartridges are used. The desiccant cartridge resembles a conventional motor vehicle spin-on oil filter in a form of a canister with a load plate having a centrally threaded bore such that the entire unit is threaded onto an upstanding boss on a mounting surface. In some installations, this type of air dryer has a significant disadvantage; namely, that access to the cartridge is severely restricted due to the confined areas where the air dryer is mounted. This confinement makes it difficult to engage the desiccant cartridge using removal tools such as the band type wrenches typically used. Other types of air dryers require substantial disassembly to access the desiccant material. These types increase maintenance time and therefore, costs.

[0006] Germany patent DE 4339758 shows an air dryer wherein a single bolt extends through the air dryer to secure the air dryer to a surface. The single bolt is accessible from the top of the air dryer. U.S. Patent 4,487,617 shows an air dryer wherein a plurality of bolts are used to secure together the air dryer housing, a bottom plate and an end cover which includes an inlet port and a delivery port. The bottom plate is clamped between a circumferentially extending lip on the air dryer housing and the end cover by a plurality of circumferentially spaced bolts.

[0007] In view of the foregoing, there is a need to provide an air dryer having an improved desiccant cartridge attachment system which allows convenient mounting and removal of the desiccant cartridge, with reduced access requirements.

### SUMMARY OF THE INVENTION

[0008] In accordance with the present invention there is provided an air dryer assembly for a motor vehicle air supply system, comprising:

a cartridge having a cup shaped outer shell, said cartridge having a desiccant material therein for removing water from air passing through said air supply system,  
a load plate having air flow passages therethrough and including a mounting surface;  
a body assembly having a plurality of ports for connection with said air supply system and a mounting surface enabling said cartridge load plate mounting surface to be mated thereto, whereby said cartridge and said body assembly cooperate to form air flow passageways for the air passing through said body assembly ports, characterized in that said outer shell is affixed to said load plate by a

rolled perimeter band, said load plate including a first threaded means;

a through bore opening in said body mounting surface and in an exposed opposing surface of said body assembly, said through bore being aligned with said cartridge load plate first threaded means when said cartridge and said body assembly are mated together at said mounting surfaces, and a single retention bolt positioned through said body assembly bore and having second threaded means engaging said cartridge load plate first threaded means thereby fastening together said cartridge and said body assembly, said retention bolt having a driving head accessible at said body assembly exposed surface.

[0009] The removable desiccant cartridge is mounted in place by a through bolt passing through the air dryer body assembly and threading into a centrally disposed threaded bore in the desiccant cartridge. The retention bolt is accessible from the exposed bottom of the body assembly which is generally unobstructed since clearance must be present for a number of air lines to be connected to that part of the device. Interlocking engagement between the desiccant cartridge and body assembly prevents these two components from rotating relative from one another during the process of mounting and dismounting the cartridge.

[0010] Further objects, features and advantages of the invention will become apparent from a consideration of the following description and the appended claims when taken in connection with the accompanying drawings.

#### BRIEF DESCRIPTION OF THE DRAWINGS

[0011] Figure 1 is an exploded elevational view of an air dryer in accordance with the present invention.

[0012] Figure 2 is a cross-sectional view through the air dryer of Figure 1 showing the air dryer assembled and internal components of the device.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

[0013] An air dryer in accordance with the present invention is shown in Figures 1 and 2 and is generally designated by reference number 10. Air dryer 10 is particularly suited for use in an air supply system for motor vehicle air brakes, such as found in heavy duty trucks. Air dryer 10 principally comprises two detachable components; namely, desiccant cartridge 12 and body assembly 14.

[0014] Details of the construction of desiccant cartridge 12 are best described with reference to Figure 2. Cartridge 12 has a drawn sheet metal cup-shaped outer shell 16. Double-wall inner sleeve 18 is disposed within outer shell 16 and defines a radial clearance passage-

way 20 around its outer perimeter, and further defines an annular interior cavity 22. Disposed within the inside cylindrical surface of inner sleeve 18 is desiccant bed 24. Desiccant bed 24 is comprised of a bead like granular material which has hydrophilic properties. The material comprising desiccant bed 24 is compressed by spring 26 and is retained by cloth sack 28 covering the upper and lower ends of the desiccant bed. Cloth sack 28 is maintained in position by O-rings 30 and 32. Spring 26 maintains desiccant bed 24 in a densely packed condition for optimal performance.

[0015] Air dryer cartridge outer shell 16 and inner sleeve 18 are affixed to load plate 34. As shown, outer shell 16 is affixed to load plate 34 by a rolled perimeter band 36. Load plate 34 has a bottom mounting surface 35 for mating with body assembly 14. O-rings 38, 40 and 42 are used to provide isolated volumes within cartridge 12, as will be described in greater detail below. At the center of load plate 34 is internally threaded boss 44. Apertures around boss 44 create a flow passageway 46. An outer groove 48 in the bottom surface of load plate 34 communicates with cartridge outer passageway 20 through internal passageways (not shown). O-rings 50, 52 and 54 are positioned within concentric grooves on the bottom surface of load plate 34 for sealing engagement with features of body assembly 14, as will be described in greater detail as follows. Porous filter 56 is positioned in the upper portion of cartridge outer passageway 20 and performs a filtration function, collecting particulates and oil.

[0016] Body assembly 14 forms a top mounting surface 57 for mating with load plate surface 35. Body assembly 14 further defines supply port 58 which receives compressed air from the system air compressor (not shown). Control port 60 receives a compressor control air signal which actuates the system compressor to cycle between a loaded mode producing compressed air and an unloaded mode. Delivery port 62 discharges de-watered compressed air. Purge valve assembly 64 is positioned within purge port 66 in the bottom surface of body casting 68 and communicates with supply port 58 and control port 60.

[0017] Body casting 68 defines three separate concentric internal cavities. Outer cavity 70 in the form of a perimeter groove is positioned between O-rings 50 and 52, and opens between the O-rings. Intermediate cavity 72 surrounds up-standing central boss 74 which is hollow, defining central passage 76. A radially drilled bore 78 communicates central passage 76 with delivery port 62, having check valve 80 installed therein. A small orifice 82 communicates intermediate cavity 72 with bore 78.

[0018] Cartridge 12 and body assembly 14 are fastened together by tightening bolt 84 having threaded end 85. The action of torquing bolt 84 pulls cartridge 12 and body assembly 14 tightly together with their mating surfaces 35 and 57 in sealing engagement. Cartridge 12 is prevented from rotating by interlocking between

tabs 86 and features on body casting 68. Snap ring 88 installed on bolt 84 serves a retention function which will be explained later. Bolt 84 further features driving head 90 which can be engaged by a wrench or socket. When cartridge 12 is mounted, compression of O-rings 50, 52 and 54 creates distinct chambers, each partly comprised by cartridge 12 and body assembly 14. Specifically, body outer cavity 70 communicates with cartridge outer passageway 20, lower body intermediate cavity 72 communicates with cartridge annular interior cavity 22, and desiccant bed 24 communicates with central passage 76.

[0019] Operation of air dryer 10 will now be described. In the loaded mode, the system compressor supplies high pressure air to supply port 58. This air passes through purge valve assembly 64 and into body outer cavity 70 and into cartridge outer passageway 20. Air thus flows upwardly through filter 56 where particulate contaminants and oil are stripped from the air flow. Air then passes to the top of outer shell 16 and downwardly through desiccant bed 24 which strips water from the compressed air. The dry air then passes around threaded boss 44, through apertures 46 and into body central passage 76. The clean dry air then exits through check valve 80 and delivery port 62. During the compressor loaded mode, this high pressure air is allowed to flow through orifice 82 into an integral purge volume defined by body intermediate cavity 72 and cartridge inner sleeve annular interior cavity 22. Thus, this purge volume reaches the pressure of air flowing from delivery port 62.

[0020] In operation of air dryer 10 in a vehicle air supply system, once the pressure in the system's reservoir (not shown) has reached a set point, a high pressure air signal is sent to a compressor control port causing it to cycle to the unloaded mode and to air dryer control port 60. An internal diaphragm within purge valve assembly 64 closes supply port 58 and opens body outer chamber 70 to atmosphere through purge port 66. Air cannot escape the unit through delivery port 62 due to the action of check valve 80. When this occurs, the compressed air stored within the purge volume slowly leaks from orifice 82 toward purge valve assembly 64, generating a reverse air flow upwardly through body central passage 76 and desiccant bed 24. This reverse purging air flow causes water to be stripped from the desiccant bed as well as some oil and solid contaminants from filter 56 which are expelled through purge valve assembly 64.

[0021] A principal feature of the present invention is the convenient manner of attachment of desiccant cartridge 12 to body assembly 14. Figure 2 illustrates the fully assembled configuration of air dryer 10. When it is desired to remove desiccant cartridge 12, retention bolt driving head 90 is accessed using a conventional hex socket. Driving head 90 is externally accessible at the exposed bottom surface of body assembly 14. Unthreading of bolt 84 occurs while interlocking between tabs 86 and body casting 68 prevent relative rotation be-

tween the cartridge and body assembly. Once bolt 84 is entirely unthreaded from boss 44, the bolt drops down with snap ring 88 preventing the bolt from falling completely out of the body assembly, keeping it from becoming lost if it were allowed to fall out. Desiccant cartridge 12 is then simply lifted off the mounting surface 57 of body assembly 14 and replaced with a new or refurbished cartridge. The new cartridge is indexed to interlock tabs 86 with body casting 68. Thereafter, bolt 84 is meshed with threaded boss 44 and the bolt is tightened.

[0022] The attachment system provided by air dryer 10 for desiccant cartridge 12 facilitates access in tight packaging installations. No tools are required to engage desiccant cartridge 12 such as conventional band type canister removal tools which require significant access area for use. Since air lines are connected with ports 58, 60 and 62 in body assembly 14, that area is relatively unobstructed in normal installations, consequently providing access of a tool to bolt driving head 90.

[0023] It is to be understood that the invention is not limited to the exact construction illustrated and described above, but that various changes and modifications may be made without departing from the scope of the invention as defined in the following claims.

#### Claims

1. An air dryer assembly for a motor vehicle air supply system, comprising:

a cartridge (12) having a cup shaped outer shell (16), said cartridge (12) having a desiccant material (24) therein for removing water from air passing through said air supply system, a load plate (34) having air flow passages (46, 48) therethrough and including a mounting surface (35);

a body assembly (14) having a plurality of ports (58, 60, 62) for connection with said air supply system and a mounting surface (57) enabling said cartridge load plate mounting surface (35) to be mated thereto, whereby said cartridge (12) and said body assembly (14) cooperate to form air flow passageways (70, 72, 76) for the air passing through said body assembly ports (58, 60, 62), **characterized in that** said outer shell (16) is affixed to said load plate (34) by a rolled perimeter band (36), said load plate (34) including a first threaded means (44); a through bore opening (76) in said body mounting surface (57) and in an exposed opposing surface of said body assembly (14), said through bore (76) being aligned with said cartridge load plate first threaded means (44) when said cartridge (12) and said body assembly (14) are mated together at said mounting surfaces (35, 57), and

- a single retention bolt (84) positioned through said body assembly bore (76) and having second threaded means (85) engaging said cartridge load plate first threaded means (44) thereby fastening together said cartridge (12) and said body assembly (14), said retention bolt (84) having a driving head (90) accessible at said body assembly (14) exposed surface.
2. An air dryer system according to claim 1 further comprising, said cartridge (12) and said body assembly (14) having interlocking means for preventing relative rotation between said cartridge (12) and said body assembly (14).
  3. An air dryer system according to Claim 2 wherein said interlocking means comprises at least one tab projecting from said cartridge load plate (34) engaging a recess formed by said body assembly (14).
  4. An air dryer according to Claim 1 wherein said cartridge (12) is mounted above said body assembly (14) with said load plate (34) defining the bottom surface (35) of said cartridge (12) and said body mounting surface (57) defining a top surface of said body assembly (14).
  5. An air dryer according to Claim 1 wherein said retention bolt (84) further having means (88) for restricting removal of said bolt (84) from said through bore (76) when said cartridge (12) is dismounted from said body assembly (14).
  6. An air dryer according to Claim 1 wherein said body assembly through bore (76) further defines air flow passage within said body assembly (14).
  7. An air dryer according to Claim 1 wherein said cartridge load plate first threaded means comprises a threaded bore (44), and said retention bolt second threaded means comprises an externally threaded end (85) of said bolt (84).
- Patentansprüche**
1. Trocknungsanordnung für ein Kraftfahrzeug-Luftversorgungssystem, die folgendes umfaßt:  
 eine Patrone (12) mit einer becherförmigen Außenschale (16), wobei die Patrone (12) darin ein Trockenmittel (24) zur Entfernung von Wasser aus durch das Luftversorgungssystem strömender Luft aufweist,  
 eine Ladeplatte (34) mit Luftströmungsdurchgängen (46, 48) durch sie hindurch und mit einer Befestigungsfläche (35);  
 eine Körperanordnung (14) mit mehreren Öffnungen (58, 60, 62) zur Verbindung mit dem Luftversorgungssystem und einer Befestigungsfläche (57), die das Zusammenfügen der Befestigungsfläche (35) der Patronenladeplatte damit ermöglicht, wodurch die Patrone (12) und die Körperanordnung (14) zur Bildung von Luftströmungsdurchgängen (70, 72, 76) für die durch die Körperanordnungsöffnungen (58, 60, 62) strömende Luft zusammenwirken, **dadurch gekennzeichnet, daß**  
 die Außenschale (16) durch ein gebogenes Umfangsband (36) an der Ladeplatte (34) befestigt ist, wobei die Ladeplatte (34) ein erstes Gewindemittel (44) enthält;  
 eine Durchgangsbohrungsöffnung (76) in der Körperbefestigungsfläche (57) und in einer freiliegenden gegenüberliegenden Fläche der Körperanordnung (14) vorgesehen ist, wobei die Durchgangsbohrung (76) auf das erste Gewindemittel (44) der Patronenladeplatte ausgerichtet ist, wenn die Patrone (12) und die Körperanordnung (14) an den Befestigungsflächen (35, 57) zusammengefügt sind, und eine einzelne Halteschraube (84) durch die Körperanordnungsbohrung (76) angeordnet ist und ein zweites Gewindemittel (85) aufweist, das das erste Gewindemittel (44) der Patronenladeplatte in Eingriff nimmt, wodurch die Patrone (12) und die Körperanordnung (14) aneinander befestigt werden, wobei die Halteschraube (84) einen Antriebskopf (90) aufweist, der an der freiliegenden Fläche der Körperanordnung (14) zugänglich ist.
  2. Lufttrocknungssystem nach Anspruch 1, bei dem weiterhin die Patrone (12) und die Körperanordnung (14) ein Verriegelungsmittel zur Verhinderung einer relativen Drehung zwischen der Patrone (12) und der Körperanordnung (14) aufweisen.
  3. Lufttrocknungssystem nach Anspruch 2, bei dem das Verriegelungsmittel mindestens eine Nase umfaßt, die von der Patronenladeplatte (34) ragt und in eine durch die Körperanordnung (14) gebildete Aussparung eingreift.
  4. Lufttrockner nach Anspruch 1, bei dem die Patrone (12) über der Körperanordnung (14) angebracht ist, wobei die Ladeplatte (34) die untere Fläche (35) der Patrone (12) und die Körperbefestigungsfläche (57) eine obere Fläche der Körperanordnung (14) definiert.
  5. Lufttrockner nach Anspruch 1, bei dem die Halteschraube (84) weiterhin ein Mittel (88) zur Beschränkung des Entfernens der Schraube (84) aus der Durchgangsbohrung (76) bei Abmontieren der

Patrone (12) von der Körperanordnung (14) definiert.

6. Lufttrockner nach Anspruch 1, bei dem die Durchgangsbohrung (76) der Körperanordnung weiterhin einen Luftströmungsdurchgang in der Körperanordnung (14) definiert.
7. Lufttrockner nach Anspruch 1, bei dem das erste Gewindemittel der Patronenladeplatte eine Gewindebohrung (44) und das zweite Gewindemittel der Halteschraube ein ein Außengewinde aufweisen des Ende (85) der Schraube (84) umfaßt.

#### Revendications

1. Ensemble de dessiccateur d'air pour un système d'alimentation en air d'un véhicule à moteur, comprenant :

une cartouche (12) ayant une coque extérieure (16) en forme de coupelle, ladite cartouche (12) contenant un matériau dessicatif (24) destiné à éliminer l'eau de l'air passant à travers ledit système d'alimentation en air,

une plaque de chargement (34) à travers laquelle sont prévus des passages (46, 48) d'écoulement d'air, et comportant une surface de montage (35) ;

un ensemble de corps (14) ayant une pluralité d'orifices (58, 60, 62) destinés à la connexion audit système d'alimentation en air et une surface de montage (57) permettant d'y accoupler la surface de montage (35) de ladite plaque de chargement de la cartouche, ladite cartouche (12) et ledit ensemble de corps (14) coopérant pour former des passages (70, 72, 76) d'écoulement d'air pour l'air passant à travers lesdits orifices (58, 60, 62) de l'ensemble de corps, **caractérisé en ce que** ladite coque extérieure (16) est fixée à ladite plaque de chargement (34) par une bande périphérique laminée (36), ladite plaque de chargement (34) comportant un premier moyen fileté (44) ;

une ouverture à alésage traversant (76) dans ladite surface de montage (57) du corps et dans une surface en regard exposée dudit ensemble de corps (14), ledit alésage traversant (76) étant aligné avec ledit premier moyen fileté (44) de la plaque de chargement de la cartouche lorsque ladite cartouche (12) et ledit ensemble de corps (14) sont accouplés l'un à l'autre au niveau desdites surfaces de montage (35, 37), et

un unique boulon de retenue (84) positionné à travers ledit alésage (76) de l'ensemble de corps et ayant un deuxième moyen fileté (85)

engageant ledit premier moyen fileté (44) de la plaque de chargement de la cartouche, en fixant ainsi ladite cartouche (12) et ledit ensemble de corps (14), ledit boulon de retenue (84) ayant une tête d'entraînement (90) accessible au niveau de la surface exposée dudit ensemble de corps (14).

2. Système de dessiccateur d'air selon la revendication 1, comprenant en outre ladite cartouche (12) et ledit ensemble de corps (14) ayant des moyens d'emboîtement pour empêcher une rotation relative entre ladite cartouche (12) et ledit ensemble de corps (14).

3. Système de dessiccateur d'air selon la revendication 2, dans lequel ledit moyen d'emboîtement comprend au moins une languette saillant depuis ladite plaque de chargement (24) de la cartouche et engageant un retrait formé par ledit ensemble de corps (14).

4. Dessiccateur d'air selon la revendication 1, dans lequel ladite cartouche (12) est montée par-dessus ledit ensemble de corps (14), ladite plaque de chargement (34) définissant la surface du fond (35) de ladite cartouche (12) et ladite surface de montage du corps (57) définissant une surface supérieure dudit ensemble de corps (14).

5. Dessiccateur d'air selon la revendication 1, dans lequel ledit boulon de retenue (84) comporte en outre un moyen (88) pour empêcher le retrait dudit boulon (84) dudit alésage traversant (76) lorsque ladite cartouche (12) est démontée dudit ensemble de corps (14).

6. Dessiccateur d'air selon la revendication 1, dans lequel ledit alésage traversant (76) dudit ensemble de corps définit en outre un passage d'écoulement d'air dans ledit ensemble de corps (14).

7. Dessiccateur d'air selon la revendication 1, dans lequel le premier moyen fileté de ladite plaque de chargement de la cartouche comprend un alésage fileté (44), et ledit deuxième moyen fileté du boulon de retenue comprend une extrémité à filetage externe (85) dudit boulon (84).




Fig-1




Fig - 2